

- sealing system for penetrations
- to install in **preinstalled pipe sleeve** or **core bore in waterproof concrete** (white tank)
- for **several multi-lines**
- split version for **retrofit installation**

DOYMA
GRIP



Product benefits

- simple installation due to precise dimensions, large sealing ranges
- permanently leakproof without retensioning (maintenance-free)
- high sealing capability in terms of the gasket insert due to **DOYMA-Grip**
- watertight welded bolts
- to be subsequently installed around the existing line

25
Years
Guarantee

Technical details

- gas-tight
- accepts angular deviations of service duct up to 8°
- accepts axial movements
- double sealing
- split

The gasket insert consists of:

- split frame rings:
 - o electro-galvanised, yellow passivated and sealant coated;
 - o optionally made of stainless steel grade 304 (1.4301) or grade 316 (1.4571/1.4404)
- elastomer:
 - o 2 x 27 mm EPDM seal rings (**DOYMA-Grip**), optionally EPDM-300 (for potable water), NBR (fuel/oil-resistant) or silicon resistant to high temperatures) or FPM (chemical resistant)
 - o 3 mm EPDM thick orange-coloured centre ring

pipe external diameter from - to	no. of pipes/cables	pipe sleeve/ core bore diameter D ₁ [NB in mm]
1 - 21	1 - 3	80 (78,5 - 83)
4 - 37	1 - 2	100 (98,5 - 104)
4 - 26	1 - 4	
1 x 18 - 36 2 x 8 - 16	1 - 3	
1 x 8 - 22 4 x 8 - 16	1 - 5	125 (123,5 - 128)
4 - 32	1 - 4	
25 - 41	1 - 3	150 (148,5 - 153)
2 x 2 - 46 2 x 2 - 36	1 - 4	
15 - 31	1 - 9	200 (199 - 204)
L_p (max. overall length): 90 mm		
We supply gasket inserts in other sizes. Please call us.		

