

Curaflex® C/0

against pressing water

- sealing system for penetrations
- to install in **preinstalled pipe sleeve** or **core bore in waterproof concrete** (white tank)
- permanent **blind sealing**



Product benefits

- simple installation due to precise dimensions, large sealing ranges
- permanently leakproof without retensioning (maintenance-free)
- high sealing capability in terms of the gasket insert due to **DPS*** and **DOYMA-Grip**
- watertight welded bolts



25 Years Guarantee

Technical details

- gas-tight
- double sealing „blind“

The gasket insert consists of:

- frame rings: asymmetrically profiled steel rings (DPS*), electro-galvanised, yellow passivated and sealant coated; optionally made of stainless steel grade 304 (1.4301) or grade 316 (1.4571/1.4404)
- elastomer: 2 x 27 mm EPDM seal rings (**DOYMA-Grip**), optionally EPDM-POD (for potable water), NBR (fuel/oil-resistant) or silicon (resistant to high temperatures) or FPM (chemical resistant)
- 3 mm EPDM thick orange-coloured centre ring

* DPS up to NB 350

NB pipe sleeve/ core bore [mm]	
50	(49 - 53)
80	(78,5 - 83)
100	(98,5 - 104)
125	(123,5 - 128)
150	(148,5 - 153)
200	(199 - 204)
250	(247 - 253)
300	(297 - 304)
350	(347 - 354)
400	(397 - 404)
450	(447 - 454)
500	(497 - 503)
600	(597 - 603)
700	(697 - 703)
L_D (max. overall length) [mm]: 90	
Other sizes, materials and customised versions on request!	

